




MALE END VIEW



- 1 = WHITE/ORANGE
- 2 = ORANGE
- 3 = WHITE/GREEN
- 4 = GREEN
- 5 = WHITE/BROWN
- 6 = BROWN
- 7 = WHITE/BLUE
- 8 = BLUE

SPECIFICATIONS


HOUSING MATERIAL	PA UL94-V0
CONTACT MATERIAL/PLATING	BRASS/GOLD
COUPLING NUT MATERIAL	DIE-CAST ZINC
RATED CURRENT [A]	0.5 A
RATED VOLTAGE [V]	48 V
WIRE SIZE	26-22 AWG (SOLID OR STRANDED)
CABLE GRIP RANGE	5-9.7mm
TEMPERATURE RATING	-25°C to +85°C (-13°F to +185°F)
PROTECTION CLASS	IEC IP65, IP67
TRANSMISSION PERFORMANCE	CAT 6A PER IEC/PAS 61076-2-109



SOURCE DRAWING - FOR REFERENCE ONLY

NOTES:

- SUITABLE FOR 10 GBIT AS PER IEEE 802.3an

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax www.turck.us TURCK			
							
MATERIAL	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	DRFT	RDS	DATE	09/07/11	DESCRIPTION CMB SX 8181-0	
SEE SPECIFICATIONS		APVD	A.A.	SCALE	1=.8		
FINISH		UNIT OF MEASUREMENT				IDENTIFICATION NO. U2-19270	
SEE SPECIFICATIONS		MILLIMETERS					
		CONTACT TURCK FOR MORE INFORMATION	DO NOT SCALE THIS DRAWING				REV C
		FILE: U2-19270				SHEET 1 OF 1	

C	UPDATE WIRE SIZE DESIGNATION	RDS	12/12/18	67752
REV	DESCRIPTION	BY	DATE	ECO. NO.